

ETHYLENE OXIDE EQUIPMENT LIQUIDATION

EXCHANGERS

- 80793 - 236 Sq Ft, 1'6" x 8'0", 113 tubes, CS/304/304, 100FV psi @ 500°F, 100FV psi @ 400°F, Mfg by Cembell in 1997
- 80792 - 785 Sq Ft, 1'9" x 10'0", 400 tubes, CS/304L/304L, 275 psi @ 450°F, 90 psi @ 350°F, Mfg by Southern Heat Exchangers in 1985
- 80800 - 789 Sq Ft, 1'8" x 10'0", 402 tubes, CS/304/304L, 275 psi @ 440°F, 90 psi @ 360°F, Mfg by Manning & Lewis
- 80801 - 1650 Sq Ft, 3'4" x 9'6", 1052 tubes, CS/304L/304L, 85 psi @ 150°F, 300 psi @ 275°F, Mfg by Con-Rad
- 80795 - 1870 Sq Ft, 2'0" x 20'0", 489 tubes, 304L/304L/CS, 100 psi @ 300°F, 75 psi @ 150°F, Mfg by Industrial Fab
- 80796 - 1894 Sq Ft, 2'0" x 20'0", 489 tubes, 304L/304L/CS, 100 psi @ 300°F, 100 psi @ 150°F, Mfg by Heat Exchanger
- 80790 - 2364 Sq Ft, 2'7" x 16'0", 767 tubes, 304L/304L/304L, 100 psi @ 300°F, 150 psi @ 250°F, Mfg by Heat Exchanger
- 80799 - 2450 Sq Ft, 2'7" x 16'0", 800 tubes, 304L/304/304L, 90 psi @ 325°F, 200 psi @ 220°F, Mfg by Missouri Boiler
- 80794 - 2583 Sq Ft, 2'8" x 20'0", 506 tubes, 304L/304L/304L, 200 psi @ 200°F, 200 psi @ 400°F, Mfg by Industrial Fab
- 80797 - 2650 Sq Ft, 2'8" x 20'0", 506 tubes, 304L/304L/304L, 225 psi @ 200°F, 240 psi @ 400°F, Mfg by Missouri Boiler in 1980
- 80798 - 2884 Sq Ft, 2'11" x 20'0", 561 tubes, CS/304L/304L, 275 psi @ 255°F, 275 psi @ 280°F, Mfg by Con-Rad
- 80789 - 2905 Sq Ft, 3'6" x 12'0", CS/304L/304L, 225 psi @ 250°F, 225 psi @ 300°F, Mfg by Bos-Hatten
- 80785 - 3923 Sq Ft, 3'10" x 12'0", 1723 tubes, CS/316L/316L, 300FV psi @ 450°F, 250 psi @ 700°F, Mfg by Cembell in 1997
- 80786 - 3923 Sq Ft, 3'10" x 12'0", 1723 tubes, CS/316L/316L, 300FV psi @ 450°F, 250 psi @ 700°F, Mfg by Cembell in 1998

EXCHANGERS cont.

- 80787 - 3923 Sq Ft, 3'10" x 12'0", 1723 tubes, CS/316L/316L, 300FV psi @ 450°F, 250 psi @ 700°F, Mfg by Nooter in 1998
- 80788 - 4548 Sq Ft, 4'3" x 14'4", 1112 tubes, CS/304L/304L, 150 psi @ 150°F, 250 psi @ 250°F, Mfg by Metalforms in 1989
- 80791 - 5716 Sq Ft, 3'11" x 16'0", 1820 tubes, 304L/304/304, 225 psi @ 150°F, 250 psi @ 200°F, Mfg by Southern Heat Exchange in 1985.

COLUMNS

- 80802 - 3'0" x 54'0", 304SS, 160 psi @ 300°F, packed

COMPRESSORS

- 80803 - 12653 ACFM, Mfg by Elliot, Mdl 40PH, 5500 Hp, 1778 rpm

LOUISIANA CHEMICAL EQUIPMENT CO.

P.O. BOX 1490

La Porte, TX 77572

PHONE: 281-471-4900 -or- Toll Free 1-866-289-5232

FAX: 281-470-2968

EMAIL: SALES@LCEC.COM

WEB SITE: WWW.LCEC.COM