

FORM U-1 MANUFACTURER'S DATA REPORT FOR PRESSURE VESSELS

As Required by the Provisions of the ASME Boiler and Pressure Vessel Code Rules, Section VIII, Division 1 **Corrected Copy** Page 1 of 3

1. Manufactured and certified by **Fabsco Shell & Tube, LLC, Plant Two, 2410 Industrial Road, Sapulpa, Oklahoma, 74066, USA**
(Name and address of Manufacturer)

2. Manufactured for **AIR PRODUCTS MANUFACTURING, LLC., 1940 AIR PRODUCTS BLVD, ALLENTOWN, Pennsylvania, 18195, USA**
(Name and address of Purchaser)

3. Location of installation **WORLD ENERGY, PARAMOUNT, California, USA**
(Name and address)

4. Type **HORIZ.** **HEAT EXH.** **S21-13258-9**
(Horizontal, vertical, or sphere) (Tank, separator, jkt. vessel, heat exch., etc.) (Manufacturer's serial number)

N/A **S21-13258-9-1 REV 9** **11282** **2023**
(CRN) (Drawing number) (National Board number) (Year built)

5. ASME Code, Section VIII, Div. 1 **2021/ N/A** **N/A** **N/A**
[Edition and Addenda, if applicable (date)] (Code Case Number) [Special Service per UG-120(d)]

Items 6-11 incl. to be completed for single wall vessels, jackets of jacketed vessels, shell of heat exchangers, or chamber of multichamber vessels.

6. Shell: (a) Number of course(s) **1** (b) Overall length **12' 10.8125"**

Course(s)			Material	Thickness		Long. Joint (Cat. A)			Circum. Joint (Cat. A, B, & C)			Heat Treatment	
No.	Diameter	Length	Spec./Grade or Type	Nom.	Corr.	Type	Full, Spot, None	Eff.	Type	Full, Spot, None	Eff.	Temp.	Time
1	16" OD	12' 10.8125"	SA-106B	3/8"	1/8"	S	NONE	1.00	1	SPOT	1.00	N/A	N/A

Body Flanges on Shells												
No.	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Location	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, thk)	Washer Material
1	N/A	15.2500"	21.1250"	4 3/16"	N/A	SA-350LF2CL1	WELDED	END	28 - 7/8"	SA-193-B7	7/8" O.D.	F-436-1

7. Heads: (a) **SA-234WPB** (b) **N/A**
(Material spec. number, grade or type) (H.T. - time and temp.) (Material spec. number, grade or type) (H.T. - time and temp.)

	Location (Top, Bottom, Ends)	Thickness		Radius		Elliptical Ratio	Conical Apex Angle	Hemispherical Radius	Flat Diameter	Side to Pressure		Category A		
		Min.	Corr.	Crown	Knuckle					Convex	Concave	Type	Full, Spot, None	Eff.
(a)	END	3/8"	1/8"	N/A	N/A	2:1	N/A	N/A	N/A		X	S	None	1.00

Body Flanges on Heads												
No.	Location	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, thk)	Washer Material
(a)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		N/A	N/A	N/A

8. Type of jacket **N/A** Jacket closure **N/A**
(Describe as ogee & weld, bar, etc.)

If bar, give dimensions; if bolted, describe or sketch **N/A**

9. MAWP **405 psi** **15 psi** at max. temp. **300 °F** **300 °F** Min. design metal temp. **5 °F** at **405 psi**
(Internal) (External) (Internal) (External)

10. Impact test **NO, EXEMPT PER UG-20(f), UCS-66(a,c,g), FIG. UCS-66 GENERAL NOTE(c), UCS-67** at test temperature of **N/A**
[Indicate yes or no and the component(s) impact tested]

11. Hydro., pneu., or comb. test pressure **HYDRO at 631/527** Proof test **N/A**

Items 12 and 13 to be completed for tube sections.

12. Tubesheet **SA-516-70N** **17.7500"** **2"** **1/8"** **BOLTED**
[Stationary (material spec. no.)] [Diameter (subject to press.)] (Nominal thickness) (Corr. allow.) Attachment (welded or bolted)

N/A **N/A** **N/A** **N/A** **N/A**
[Floating (material spec. no.)] (Diameter) (Nominal thickness) (Corr. allow.) (Attachment)

13. Tubes **SA-179** **3/4"** **0.083"** **60** **U**
(Material spec. no., grade or type) (O. D.) (Nominal thickness) (Number) [Type (Straight or U)]

Manufactured by Fabsco Shell & Tube, LLC, Plant Two, 2410 Industrial Road, Sapulpa, Oklahoma, 74066, USA

Manufacturer's Serial No. S21-13258-9

CRN N/A

National Board No. 11282

Items 14-18 incl. to be completed for inner chambers of jacketed vessels or channels of heat exchangers.

14. Shell: (a) No. of course(s) 1

(b) Overall length 1' 10"

Course(s)			Material		Thickness		Long. Joint (Cat. A)			Circum. Joint (Cat. A, B, & C)			Heat Treatment	
No.	Diameter	Length	Spec./Grade or Type		Nom.	Corr.	Type	Full, Spot, None	Eff.	Type	Full, Spot, None	Eff.	Temp.	Time
1	16" OD	1' 10"	SA-106B		3/8"	1/8"	S	NONE	1.00	1	FULL	1.00	N/A	N/A

Body Flanges on Shells

No.	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Location	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, thk)	Washer Material
2	N/A	15.2500"	21.1250"	4 3/16"	N/A	SA-350LF2CL1	WELDED	ENDS	28 - 7/8"	SA-193-B7	7/8" O.D.	F-436-1

15. Heads: (a) SA-516-70

(Material spec. number, grade or type) (H.T. - time and temp.)

(b) N/A

(Material spec. number, grade or type) (H.T. - time and temp.)

	Location (Top, Bottom, Ends)	Thickness		Radius		Elliptical Ratio	Conical Apex Angle	Hemispherical Radius	Flat Diameter	Side to Pressure		Category A		
		Min.	Corr.	Crown	Knuckle					Convex	Concave	Type	Full, Spot, None	Eff.
(a)	END	2 1/8"	1/8"	N/A	N/A	N/A	N/A	N/A	21 1/8"			S	None	1.00

Body Flanges on Heads

No.	Location	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, thk)	Washer Material
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

16. MAWP 405 psi 15 psi at max. temp. 330 °F 300 °F Min. design metal temp. 32 °F at 405 psi.
(Internal) (External) (Internal) (External)

17. Impact test NO, EXEMPT PER UG-20(f), UCS-66(a,c,g), FIG. UCS-66 GENERAL NOTE(c), UCS-67 at test temperature of N/A.
[Indicate yes or no and the component(s) impact tested]

18. Hydro., pneu., or comb. test pressure Hydro. at 631/527 Proof test N/A

19. Nozzles, inspection, and safety valve openings:

Purpose (Inlet, Outlet, Drain, etc.)	No.	Diameter or Size	Type	Material		Nozzle Thickness		Reinforcement Material	Attachment Details		Location (Insp. Open.)
				Nozzle	Flange	Nom.	Corr.		Nozzle	Flange	
INLET/OUTLET	1/1	6"-600#	RF WN	SA-106B	SA-350LF2CL1	XH	1/8"	SA-516-70	UW16.1	WELDED	SHELL
INLET/OUTLET	1/1	3"-600#	RF LWN		SA-350LF2CL1	0.88"	1/8"	SA-516-70	UW16.1	WELDED	CHANNEL
VENT/DRAIN	1/1	2"-300#	RF LWN		SA-350LF2CL1	0.63"	1/8"		UW16.1	WELDED	CHANNEL
AUX	3	2"-300#	RF LWN		SA-350LF2CL1	0.63"	1/8"		UW16.1	WELDED	SHELL NOZS.
AUX	2	2"-300#	RF LWN		SA-350LF2CL1	0.63"	1/8"		UW16.1	WELDED	CHANNEL NOZS.

20. Supports: Skirt No Lugs NONE Legs NONE Others 2 SADDLES Attached WELDED TO SHELL
(Yes or no) (Number) (Number) (Describe) (Where and how)

21. Manufacturer's Partial Data Reports properly identified and signed by Commissioned Inspectors have been furnished for the following items of the report (list the name of part, item number, Manufacturer's name, and identifying number):

N/A

22. Remarks

SERVICE: STRIPPER FEED / DEBUTANIZER BOTTOMS EXCHANGER ITEM: 18-X-372A

Manufactured by Fabsco Shell & Tube, LLC, Plant Two, 2410 Industrial Road, Sapulpa, Oklahoma, 74066, USAManufacturer's Serial No. S21-13258-9CRN N/ANational Board No. 11282

CERTIFICATE OF SHOP COMPLIANCE

We certify that the statements in this report are correct and that all details of design, material, construction, and workmanship of this vessel conform to the ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. U Certificate of Authorization Number 30112 Expires December 30, 2024

Date 08/05/2024

Name _____

Fabsco Shell & Tube, LLC, Plant Two

Signed _____

(Manufacturer)

(Representative)

CERTIFICATE OF SHOP INSPECTION

I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and employed by

Bureau Veritas Inspection and Insurance Company, of Lynn, MA

have inspected the pressure vessel described in this Manufacturer's Data Report on October 25, 2023, and state that,

to the best of my knowledge and belief, the Manufacturer has constructed this pressure vessel in accordance with ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. By signing this certificate neither the Inspector nor his/her employer makes any warranty, expressed or implied, concerning the pressure vessel described in this Manufacturer's Data Report. Furthermore, neither the Inspector nor his/her employer shall be liable in any manner for any personal injury or property damage or a loss of any kind arising from or connected with this inspection.

Date 08/05/2024

Signed _____

(Authorized Inspector)

Commissions: _____

16613

(National Board Authorized Inspector Commission number)

CERTIFICATE OF FIELD ASSEMBLY COMPLIANCE

We certify that the statements made in this report are correct and that the field assembly construction of all parts of this vessel conforms with the requirements of ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. U Certificate of Authorization Number _____ Expires _____

Date _____

Name _____

(Assembler)

Signed _____

(Representative)

CERTIFICATE OF FIELD ASSEMBLY INSPECTION

I, the undersigned, holding a valid commission issued by The National Board of Boiler and Pressure Vessel Inspectors and employed by _____,

have compared the statements in this Manufacturer's Data Report with the described pressure vessel and state that parts referred to as data items _____, not included in the certificate of shop inspection, have been inspected by me and to the best of my knowledge and belief, the Manufacturer has constructed and assembled this pressure vessel in accordance with the ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. The described vessel was inspected and subjected to a pressure test of _____. By signing this certificate neither the Inspector nor his/her employer makes any warranty, expressed or implied, concerning the pressure vessel described in this Manufacturer's Data Report. Furthermore, neither the Inspector nor his/her employer shall be liable in any manner for any personal injury or property damage or a loss of any kind arising from or connected with this inspection.

Date _____

Signed _____

(Authorized Inspector)

Commission _____

(National Board Authorized Inspector Commission number)